

CROSS-REFERENCE TO RELATED APPLICATION

Applicant claims priority from British application GB 0101436.4 filed 19 January 2001.

BACKGROUND OF THE INVENTION

5 This invention relates to home entertainment and data systems, in which a number of consumer electronic devices are interconnected by the system. For example, consumer devices may include television sets, a VCR (video cassette recorder), a stereo system, a DVD player, a video game player, an Internet terminal device, and security cameras.

10 A television set used to be a simple device for users to set up and connect. However, numerous other consumer electronic devices may now be connected to a television set, which complicates the connections and which also may degrade the signal quality within a system. In particular, the video carrier signal from an antenna, cable television system, or satellite TV dish is a modulated high
15 frequency signal of a frequency over 50 MHz. In the U.S., the lowest VHS broadcast signal is channel 2 with a frequency of 54 to 60 MHz. Each U.S. prior (not HDTV) color channel has a bandwidth of about 6 MHz. The highest definition proposed for high quality HDTV (high definition TV) has a bandwidth of about 30 MHz, so video baseband is almost always under 40 MHz. Carrier signals for
20 HDTV are at a nominal frequency of well over 100 MHz.

A modulated carrier signal is conventionally carried by a coaxial cable because a coaxial cable has the required bandwidth capacity. The video carrier signal is demodulated by the tuner of a TV receiver to produce a video channel of baseband frequency (under 40 MHz) that is converted to a video image by the
25 monitor portion of the television set. Baseband frequencies are less than 40 MHz, while video carrier frequencies are more than 50 MHz. A baseband signal which

represents one TV channel, does not have to be demodulated for display on a monitor, while a carrier TV signal is normally modulated with many channels and must be demodulated to obtain a channel for display.

5 In the past, a VCR would be connected to a television set using a coaxial cable and connectors carrying the high frequency UHF or VHF signals. The VCR would demodulate the signal to enable the signal to be recorded. When the recorded signal was played, it would have be remodulated to UHF frequencies before being transferred to the TV set over a coaxial cable. These multiple conversions are a source of noise. The more recent use of RCA AV connectors enables baseband signals to be transmitted between TV and VCR's, which reduces the noise problem. However, coaxial cables carrying UHF signals are still used for providing multiple TV outlets in different rooms in a home. This requires wide band amplification of the frequencies of interest before their distribution around the home.

10
15 The physical connection of multiple devices in order to realize the full benefit of each component of a home entertainment system can be difficult, with a variety of types of connectors required for different devices.

SUMMARY OF THE INVENTION

20 In accordance with one aspect of the present invention, a home entertainment system backbone is provided which includes a hub having a plurality of TV tuners which each receives a carrier signal (modulated and over 50 MHz) modulated by a plurality of video channels, wherein the output of each TV tuner is a baseband (under 40 MHz with the video channel not modulated) video signal. The hub includes a switching matrix which has supply ports where the matrix receives the outputs of the TV tuners, and outputs of security cameras, etc. and
25 delivers control signals to such TV tuners, etc. to select a channel, etc. The

switching matrix also has consumer ports from which video channel signals are delivered to a selected TV monitor in a room for viewing and where control signals such from a remote control in the room are delivered to the switching matrix to control a TV tuner, etc. The switching matrix enables different ports to be coupled together to transmit signals between the different ports.

The architecture of the system enables the hub to be provided with one or more video carrier signals, typically over a coaxial cable, from an ariel, cable system, or satellite dish. All of the TV tuners used by the entertainment system are in the hub, so the distribution signals around the system, representing the different video channels, can take place at baseband frequencies (under 40 MHz). The switching matrix enables video generating consumer devices such as video recorders to be positioned in one location, except for video cameras, while enabling the signals to be connected to any chosen terminal in the home. The remote control sensors in the different rooms enable the tuners to be controlled despite their location in the hub.

Preferably, twisted pair cabling is provided between each port and the hub. This is possible because all signals from the hub are at baseband frequencies (under 40 MHz). The cabling may comprise four twisted pairs, with one twisted pair allocated to remote control signaling, one twisted pair allocated to one channel of audio, one twisted pair allocated to another channel of audio, and one twisted pair allocated to video data. The cabling may comprise balanced twisted pair cabling, such as CAT5 cabling, and each port may comprise an RJ45 port.

The terminals are distributed around the home and all connections to the terminals can be the same, regardless of the type of device to be connected to the system. One or more supply ports may be used for security cameras, and the switching matrix then enables camera images to be selectively coupled to the television monitors in the system. The hub may include means for detecting an

alarm signal on the camera signal inputs (e. g. if the camera is provided with a motion detector), and can provide such an alarm signal to a selected TV monitor.

5 The supply ports of the switching matrix are each connected to a particular baseband frequency source such as the output of a particular TV tuner. There may be more supply ports than TV tuners, security cameras, etc., which enables each source of signals (TV tuner, etc.) to be connected to a selected supply port that is connected a particular terminal in a room. The hub may include a switching arrangement for coupling a first supply port at which audio received, to multiple other consumer ports where audio outputs signals are delivered. In this way, audio such as music can routed to multiple speakers. The switching arrangement can include manual switches for manually connecting a particular supply port to a particular consumer port. The same cabling can be used for audio as for video.

10 The home entertainment system includes a plurality of TV tuners each receiving a UHF, VHF, or other high frequency (above 50 MHz) video-modulated carrier signal and each tuner demodulating the signal to baseband (under 40 MHz and not modulated to carry multiple video channels). The system includes a switching matrix having baseband inputs for consumer devices and for TV tuner signals, and baseband outputs, wherein the switching matrix enables the inputs to be selectively coupled to the outputs. The system further includes a processor for receiving control signals from the terminals to enable control of the TV tuners and to control the switching matrix to enable selected consumer devices to be coupled to selected terminals.

20 The novel features of the invention are set forth with particularity in the appended claims. The invention will be best understood from the following description when read in conjunction with the accompanying drawings.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a home entertainment system of the present invention.

Fig. 2 is a diagram showing how said a TV set or monitor is connected to the system.

Fig. 3 is a block diagram which shows an additional audio distribution system for use with the home entertainment system of Fig. 1.

Fig. 4 is an isometric view showing how speakers are connected to the system.

Fig. 5 is a block diagram view showing how consumer devices within the system can be located at any desire location.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 illustrates shows a home entertainment system of the present invention, which includes a backbone, which is the essential wiring and connection terminals of the system and consumer devices connected to the terminals. The system has a central controlling hub 10 which comprises a plurality of TV tuners 12. In Fig. 1, eight of such tuners TV 1 to TV 8 are shown. The system can thus support eight independently controllable televisions or video monitors.

A source of video signals is indicated at 14, which may be a video cable, satellite dish receiver, video antenna or the like. The video carrier signal carried on line 100 may have a frequency of hundreds or thousands of megahertz, and be modulated by numerous video channels that each have a baseband frequency of less than 40 MHz. A baseband signal is a signal that can be viewed (or heard or contain digital data used, or otherwise used) without requiring demodulation and therefore without giving rise to extra noise that is created in demodulation.

The hub receives the high frequency modulated video (and audio, data,

etc.) carrier signal input from source 14, and each tuner TV1 to TV8 demodulates the video carrier signal to produce a selected one of the multiple channels carried by the carrier signal, each channel being of baseband frequency (less than 40 MHz). Each tuner also has a stereo sound decoder, and provides a video output and audio left and right signals. Each tuner is also provided with a remote control signal reader, or channel changer device 16, which enables remote control signals to be provided to the tuners to control them by changing the tuner output to a different channel.

A plurality of room terminals 18 are provided, which are distributed around the home. Each piece of user equipment such as a TV set or monitor 52 for displaying a video signal and a controller 54 for changing channels, is connected to a terminal. It is noted that a TV set usually includes a TV tuner (demodulator) whose baseband output is delivered to a monitor-driving circuit. Applicant delivers baseband signals directly to the monitor-driving circuit, bypassing any tuner. In Fig. 1, the hub is shown as having sixteen consumer ports P1-P16 with corresponding output and input lines 21, 23 of a cable link or cabling 20. In the example shown, there are three TV monitors 52 and corresponding cable links 20 in the family room or lounge L, there are two in the master bedroom B1, two in the dining room D, and one in the kitchen K. There are also controllers 54 associated with some or all of the TV monitors.

Each room terminal 18 is connected to a consumer port P1-P16 of the hub by a cable link 20. Balanced twisted pair cabling is used, for carrying baseband (not UHF/VHF) signals. The cabling may comprise four twisted pairs, one pair allocated to remote control signaling, one pair allocated to one channel of audio, one pair allocated to another channel of audio, and one pair allocated to video signals. For example, the cabling may comprise CAT5 cabling, and each port may comprise an RJ45 socket.

5 The sixteen consumer ports P1 to P16 carry the output signals of the
switching matrix 22 (plus input control signals). The switching matrix 22 is a
baseband switching device (it carries signals under 40 MHz without modulation of
video) which enables any of the inputs at the supply ports 90 (from the tuner
10 devices TV1-TV8, VHS, cameras, etc.), to be switched to any of the outputs at the
consumer ports P1-P16 using switches that switch baseband frequencies. The
inputs to the matrix supply ports comprise the baseband TV tuner signals TV1 to
TV8 and baseband signals from other consumer devices. Fig 1 shows six camera
signal matrix inputs C1-C6 and five other device matrix inputs D1 to D5. All of the
15 inputs are connected to the supply ports 90, from which control signals can be
transmitted back to the devices that generate the signals. By way of example, a
VHS 24 for recording signals, a DVD player 26, a user video recorder 28 a satellite
receiver 30 (when 14 is an antenna) and a cable decoder 32 are shown in Fig. 1.
Although not shown, the devices may also include audio systems. In the example
20 of Fig. 1, these form part of the hub 10 although it will be apparent from the
following that these devices may be connected to video or audio monitors located
around the home if the user desires. Six cameras 34 are shown outside the hub
10. Most of the equipment in the hub is located within five meters of the switching
matrix 22 for low losses and to provide a compact system that can be stored in a
closet or small room. Most of the monitors are spaced more than five meters from
the switching matrix and hub.

25 The inputs TV1 to TV8, C-1 to C6, D1 to D5 which are connected to the
supply ports 90 of the switching matrix, and the outputs that are connected to the
consumer ports P1 to P16, all provide signals that are not only used by a monitor,
but provide signals passing in reverse from a consumer port to a supply port to
control the various sources of video or audio signals.

It is possible for the eight TV outputs at 38 to be provided directly as inputs to the switching matrix 22. In that case, each TV tuner is allocated a particular supply port 90, and the switching matrix by default connects each TV tuner to a corresponding supply port. In that case, there should be the same number of supply ports 90 dedicated to the TV tuners, as the maximum number of TV tuners 12. However, for greater flexibility, Fig. 1 shows a system with more supply ports 90 for receiving the outputs of the TV tuners, than the number of TV tuners TV1-TV8. This allows the TV tuners to be allocated to one of a plurality of different supply ports 90. For this purpose, the hub has an array 36 of connectors S1 to S16. Each connector in the array can be connected to one of the TV tuners by a linking element 38. The linking element 38 may be manually positioned (and connected) to enable the system to be configured according to requirements. This enables a patch panel system to be implemented. Thus, in the example of Fig. 1, the user has decided that tuner TV1 should be provided to consumer port P2 in the lounge L, and this is achieved by manually inserting a linking element 38 between tuner TV1 and connector S2. This decision will be based, for example, on a position of furniture in the home and on possible problems with a tuner so that another tuner can be used. Similarly, the output of tuner TV2 is provided through switch 54 to consumer port P4 that connects to a video monitor in the main bedroom B1, and so on. The hub connections connect each TV tuner to a selected connector S1-S16 and connect each connector to a correspond supply port 90. In Fig. 1, twenty-seven supply ports are shown. The default setting of the switching matrix 22 is to couple the supply ports leading from connectors S1 to S16 respectively to the consumer ports P1 to P16. This makes it easier for a person to review the system and make any changes, since the connection of each supply port 90 to a consumer port P1 to P16 lies in the switching matrix 22 whose inside workings are generally not easily viewed. Each connector and supply port

is marked with its number.

Each terminal 18 that is in use, includes a video monitor 54 (or audio, or data monitor or other device that uses the input signals) and is also provided with an infrared remote control sensor 54 that allows the viewer to select a channel (or a camera). As shown in Fig. 2, at a terminal that is in use, the audio (left and right) and the video twisted pair of signals from an RJ45 connector are provided to an AV socket 50, which connects to the TV set or monitor 54. If the TV 54 has a tuner (for receiving and demodulating a high frequency carrier signal) and a baseband input, the socket 50 is connected to the baseband input. This enables baseband signals to be provided to the TV 54 without lossy (and noisy) remodulation and demodulation to and from a high frequency carrier signal. The remote control signals are provided from a control 56 to a remote control sensor 52 for mounting on (or which is part of) the television 54. The signals from the sensor 52 are delivered over a twisted wire pair connected through a line to one of the ports P1-P16 (Fig. 1). The twisted pair for the remote signals carry duplex signals, and also carry the power to the remote control sensor 52.

The hub includes a processor 23 (Fig. 1) which receives all of the remote control signals provided along the line 22 from each terminal. The hub therefore detects all remote control choices made by the user and uses this information to control the switching matrix 22 (assuming that the matrix should be switched away from its original default configuration).

In one example, the user at the terminal 18 that is connected to the consumer port P1, selects a channel that is reserved for the video recorder 28, and the switching matrix will switch the output of connector D3 which is connected to one of the supply ports 90, to consumer port P1 and to the output line 23 at P1, which is associated with the input line 21 at P1 from which the video signal arrived. This overrides the default connection of TV1 to P1, to connect the output of D3 to

5 P1. As mentioned above, each terminal 18 is provided with a remote control signal reader 54 which may be a standard IR detector . In order to provide IR signals to the detector, the twisted pair of cable leading to the terminal 110 is provided with an LED (light emitting diode) which is fixed adjacent to the standard detector of the terminal. Thus the IR signals are converted to electrical signals at the consumer ports P1-P16 and are reconverted to IR signals at the terminals 18.

10 The system connects the remote control signals delivered over lines 23 to the consumer ports P1-P16 so the signals received by the switching matrix are permanently routed simultaneously to all of the devices that supply signals, including remote control reader 16 of the tuners TV1 - TV8, and similar remote control readers of the devices 24-32 and the cameras 34. A single remote control 54 for any device can be used in any room of the house. In a preferred arrangement, the switching matrix simply routes the remote control signal to all devices, and the device being controlled will recognize the signal whereas the other devices will not. Thus, for example, a video remote control can be used at the terminal 18 connected to consumer port P2 to control the video 28 in the hub.

15 Each video (or audio or data) generation device 24-32 has an allocated channel (or other remote control signal input) so the hub can connect the user to any desired equipment from any terminal 18. Essentially, the switching matrix function to override the normal connection of the TV tuner video and audio to the port.

20 As shown in Fig. 1, the switching matrix 22 is connected, through connectors C1-C6 and corresponding supply ports 90, to six security cameras 34. The switching matrix 22 enables camera images from any of the six cameras to be coupled to a selected one of the video monitors 52 in the system. For example, if a user should select a terminal 18 connected to consumer port P1, and switches the outputs of all six cameras (on connectors C1-C6) the switching matrix may

switch the cameras to the monitor 52 at consumer port P1 so the camera outputs appear on the monitor in a cyclical manner, such as where the output of each camera is displayed for three seconds before the output of the next camera is displayed. The user can operate the control 54 to stop the cycling and constantly display the output of one of the six cameras.

Each camera may be provided with a motion and/or sound sensor. When such motion or sound is detected, an alarm icon may be provided on the monitor 18 which has requested such alert.

The cameras 34 may not need actual RJ44 ports, as they may be installed in one positioned and remaining fixed. However, the camera control and signals are relayed using the same cabling, and could be connected to identical ports as for the remainder of the system. This may be desired if a camera location is to be changed.

Fig 3 shows an extension of the system to provide distributed audio. The extension may use the same groups of consumer ports P1-P16, or may use additional ports. In Fig. 3, the ports P1-P16 of the system can be connected to a further switching arrangement 60 for selectively coupling a first supply port at which audio is received from a consumer device, to multiple other consumer audio ports. For example, the signal at consumer port P2 is provided as an input I to the switching arrangement 60, and the four outputs O1 to O4 from the switching arrangement are connected to ports P3, P14, P15, and P16. In this way, a sound output can be provided to one supply port (at the location of an audio disc player, etc.) and the switching arrangement can route the audio signals to consumer ports to which speakers are connected. The switching arrangement 60 may be a manual device located at the hub, or at another suitable location, and enables the control of the distribution of audio. Each consumer port may have an independent volume control for the speaker signals, so that different volumes may be provided

in different rooms.

Fig. 4 shows a connector 62 for extracting the audio part from a consumer port P, which provides one twisted pair as a left speaker signal L and one twisted pair as a right speaker signal R.

5 In the example given above, the sources of video and sound are located in the hub 10. This has the advantage of short connections, which decrease noise and the amount of required amplification. However, the signal generating devices can be at any desired location. Fig. 5 shows a video recorder 28 in a room of the house and connected to consumer port P16 (to the line that carries control signals or to a duplex line that carries signals to and from the consumer port). The switching matrix 22 couples the video signal to a supply port leading to connector S16, and physical connections 70 within the hub connects the video signal to the switching matrix input D3. The signal is switched from D3 to the desired port PD by the switching matrix 22.

10
15
20
25 Numerous variations to the system will be apparent to those skilled in the art. The number of ports, the number of signal-generating devices including TV tuners and cameras supported by the system, are all by way of example only. The invention enables multiple devices to be connected together by use of low cost cabling (twisted wire pairs instead of coaxial cables) with a high degree of flexibility. The transparency of the system to IR control signals allows existing remote control devices to be used. Each device in the hub enables the remote control signals to be regenerated (for example, an LED) and directed to the IR detectors. Multiple remote controls may be combined to a single programable remote control device to enable control of a pool of devices. The devices in the hub, served to supply baseband signals to the switching matrix, and enable all cabling to be accomplished by twisted pair cabling.

5 The invention can be implemented using well known equipment. Implementation is with a baseband switching matrix and a processor which receives inputs from remote control device signals. The system can be supplemented with various designs of user interface, with menus for defining the system set up and operation.

10 Thus, the invention provides an entertainment center system that allows each person viewing one of many video monitors scattered throughout a home, to select one of numerous channels supplied by a carrier signal source such as a cable video system, in the same manner as a person viewing a television set connected directly to the cable system can select a channel. However, the system also allows each viewer to select a different source of video signals, such as the output from a DVD player, a camera, or a demodulated channel from another source such as a satellite dish or an antenna, or to even select a different TV tuner that receives the same carrier signal as the TV tuner whose output was previously viewed. This is accomplished by a hub in which a plurality of TV tuners are located, which each demodulates the output of one (or more) carrier signals and other sources, and which also includes a switching matrix. The switching matrix has a plurality of supply ports that are connected to the sources of the signals that may be desired by the person at a monitor in a room, which are primarily video signals but which also include audio signals and even data signals. The switching matrix also has a plurality of consumer ports which are connected to the terminals in the different rooms. Each port can receive and deliver a signal, to allow not only video and audio signals to be transmitted, but to allow channel-selecting control signals and other control signals to be transmitted in the opposite direction to the source, such as to the TV tuner to change the channel. Wires can be used that pass signals in opposite direction along with a duplex circuit that routes signals traveling in different direction to different circuits, although applicant generally

15
20
25

Although particular embodiments of the invention have been described and illustrated herein, it is recognized that modifications and variations may readily occur to those skilled in the art, and consequently, it is intended that the claims be interpreted to cover such modifications and equivalents.

5

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---